

POSTER PRESENTATION

Open Access

First spike latency sensitivity of spiking neuron models

Laura Trotta^{1*}, Alessio Franci², Rodolphe Sepulchre^{1,2}


From Twenty Second Annual Computational Neuroscience Meeting: CNS*2013
Paris, France. 13-18 July 2013

First spike latency is the long-lasting period preceding the first spike of a neuron submitted to a super-threshold stimulus. It has been suggested that this latency could code for stimulus recognition in several sensory systems [1,2].

To encode information reliably, first spike latency should be sensitive to sensory inputs but robust to external perturbations. This paper studies the robustness of the first spike latency in spiking neuron models. These models are nonlinear and possibly high-dimensional. Understanding which parameters govern the first spike latency sensitivity in these systems generally requires extensive numerical simulations. We

show that a local sensitivity analysis of the system is a good predictor of the global robustness of the latency code. This analysis, motivated by previous work on delayed decision-making in bistable models [3], relies on the assumption that the model possesses a saddle node bifurcation with a sufficiently attractive center manifold. Results are illustrated on a 6-dimensional model including a K^+ -current of type A [4], a current of particular importance for first spike latencies, see Figure 1.

Our results show that first spike latency coding is particularly robust for a new type of excitability called regenerative excitability [5].



* Correspondence: l.trotta@ulg.ac.be

¹Department of Electrical Engineering and Computer Science, University of Liège, Liège, 4000, Belgium

Full list of author information is available at the end of the article

Author details

¹Department of Electrical Engineering and Computer Science, University of Liège, Liège, 4000, Belgium. ²Centre de recherche Inria Lille-Nord Europe, Parc scientifique de la Haute Borne, Villeneuve d'Ascq, 59650, France.

Published: 8 July 2013

References

1. Gollisch T, Meister M: **Rapid neural coding in the retina with relative spike latencies.** *Science* 2008, **319**(5866):1108-1111.
2. Johansson RS, Birznieks I: **First spikes in ensembles of human tactile afferents code complex spatial fingertip events.** *Nat Neurosci* 2004, **7**(2):170-177.
3. Trotta L, Bullinger E, Sepulchre R: **Global analysis of dynamical decision-making models through local computation around the hidden saddle.** *PLoS One* 2012, **7**(3):e33110.
4. Connor JA, Stevens CF: **Prediction of repetitive firing behaviour from voltage clamp data on an isolated neurone soma.** *J Physiol* 1971, **213**(1):31-53.
5. Drion G, Franci A, Seutin V, Sepulchre R: **A novel phase portrait for neuronal excitability.** *PLoS One* 2012, **7**(8):e41806.

doi:10.1186/1471-2202-14-S1-P354

Cite this article as: Trotta et al.: **First spike latency sensitivity of spiking neuron models.** *BMC Neuroscience* 2013 **14**(Suppl 1):P354.

**Submit your next manuscript to BioMed Central
and take full advantage of:**

- Convenient online submission
- Thorough peer review
- No space constraints or color figure charges
- Immediate publication on acceptance
- Inclusion in PubMed, CAS, Scopus and Google Scholar
- Research which is freely available for redistribution

Submit your manuscript at
www.biomedcentral.com/submit

